



Dry Lube TECHNICAL DATA

PRODUCT OVERVIEW

A high performance lubricant designed for use on bicycle chains and drivetrains in dry and dusty conditions. It penetrates rapidly into links before the solvent evaporates leaving a thin lubricating film. This formula contains PTFE which helps to reduce friction and provide smoother gear shifting.

PRODUCT FEATURES & BENEFITS

- Contains PTFE for reduced friction
- Increases drivetrain efficiency
- Penetrates rapidly into chain links, protecting all surfaces
- Extreme pressure and anti-wear additives prolong component life
- Helps protect against corrosion
- Twist cap for variation on flow for a more precise application
- Characteristic GT85 fragrance
- Fast drying

RECOMMENDED USES

Bicycle chains
Drivetrains.

DIRECTIONS FOR USE

Ensure chain and drive-train are clean and dry. Shake bottle thoroughly before use to ensure the PTFE is fully dispersed. Twist spout to open. Apply to the inside of the chain for a better penetration, ensuring entire length is coated and leave to dry.

TECHNICAL DATA

Physical Properties

| | |
|--------------------------------|---|
| Appearance: | A cloudy straw coloured liquid with an alcoholic odour. |
| pH: | Not applicable |
| Specific Gravity: | 0.842 |
| Non Volatiles % m/m | 35-45 |
| Flammability: | Highly flammable |
| Composition Data, as supplied: | A solution of synthetic lubricant, viscosity modifier, extreme pressure and anti-wear additives, PTFE and fragrance in Isopropanol. |
| Service temperature: | Designed for use at ambient temperature. |

PACKAGING SPECIFICATIONS

| | |
|------------|----------|
| Case Code: | 44574 |
| Unit Size: | 80ml |
| Case Size: | 80ml x 6 |

